

Page 1 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Auspuff-Reparatur-Paste 200 g

Art.: 3340

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Seam sealant

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 1 - Adhesives, sealants

Process category [PROC]:

PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC 8b - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC 9 - Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Industrial use of processing aids in processes and products, not becoming part of articles

ERC 7 - Industrial use of substances in closed systems

ERC 8a - Wide dispersive indoor use of processing aids in open systems

ERC 8d - Wide dispersive outdoor use of processing aids in open systems

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr Telephone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.1.2 Classification according to Directives 67/548/EEC and 1999/45/EC (including amendments)

The mixture is not classified as dangerous in the terms of the directive 1999/45/EC.

2.2 Label elements



Page 2 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

2.2.1 Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

-	
Registration number (REACH)	
Index	-
EINECS, ELINCS, NLP	-
CAS	-
content %	
Classification according to Directive 67/548/EEC	
Classification according to Regulation (EC) 1272/2008 (CLP)	

SECTION 4: First aid measures

4.1 Description of first aid measures

Never pour anything into the mouth of an unconscious person!

Inhalation

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Ingestion

Give copious water to drink - consult doctor immediately.

Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes

with long-term contact:

Product removes fat.

Dermatitis (skin inflammation)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher

Cool container at risk with water.



Page 3 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Irritating gases

Oxides of carbon

Oxides of nitrogen

Toxic pyrolysis products.

5.3 Advice for firefighters

According to size of fire

Protective respirator with independent air supply.

Full protection, if necessary

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.2 Environmental precautions

Prevent from entering drainage system.

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store separately from alkalis.

Store separately from acids.

Store in a dry place.

Store in a well ventilated place.

Protect from direct sunlight and warming.

Only store at temperatures from 15°C to 30°C.

7.3 Specific end use(s)

No information available at present.



®·

Page 4 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemica	Il Name	general dust limit				Content %:
WEL-TWA:	10 mg/m3 (inhal. dust)	, 4 mg/m3 (respir.	WEL-STEL:			
dust)	,					
BMGV:				Other information:	,	
						2
Chemica	Il Name	Talc				Content %:
WEL-TWA:	1 mg/m3 (res. dust)		WEL-STEL:			
BMGV:				Other information:		
Chemical	ıl Name	Rockfibre				Content %:
WEL-TWA:	2 fibres/ml, 5 mg/m3 (I	:d >= 3:1, < 6µm)	WEL-STEL:			
(MMMF)	, 5 (, , ,				
BMGV:				Other information:	•	
Chemica		Barium sulphate				Content %:
WEL-TWA:	4 mg/m3 (respirable di	ust), 10 mg/m3	WEL-STEL:			
(total inhalab		, ,				
BMGV:				Other information:	•	
Chemica	ıl Name	China stone				Content %:
WEL-TWA:	2 mg/m3 (res. dust)		WEL-STEL:	 ·		
BMGV:	<u> </u>			Other information:	•	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

Recommended

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

> 0,4

Permeation time (penetration time) in minutes:

> 240

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 5 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

Respiratory protection: Normally not necessary.

Thermal hazards

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to

manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Pastelike, Solid Colour: Grey Odour: Odourless Odour threshold: Not determined pH-value: Not determined Melting point/freezing point: Not determined Initial boiling point and boiling range: Not determined Flash point: Not determined Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: ~1,92 g/cm3 Bulk density: Not determined Solubility(ies): Not determined Water solubility: partially, Soluble Partition coefficient (n-octanol/water): Not determined Auto-ignition temperature: Not determined Decomposition temperature: Not determined Not determined Viscosity: Explosive properties: Not determined

Oxidising properties:

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

Not determined

SECTION 10: Stability and reactivity

No

10.1 Reactivity

See also Subsection 10.2 to 10.6. The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6. Stable with proper storage and handling.



Page 6 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.

10.4 Conditions to avoid

See also section 7. Protect from humidity.

10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.

See also section 5.2

SECTION 11: Toxicological information

Possibly more information on health effects, see Section 2.1 (classification).

Auspuff-Reparatur-Paste 200 g Art.: 3340									
Toxicity/effect	Endpoin t	Value	Unit	Organism	Test method	Notes			
Acute toxicity, by oral route:						n.d.a.			
Acute toxicity, by dermal route:						n.d.a.			
Acute toxicity, by inhalation:						n.d.a.			
Skin corrosion/irritation:						n.d.a.			
Serious eye damage/irritation:						n.d.a.			
Respiratory or skin sensitisation:						n.d.a.			
Germ cell mutagenicity:						n.d.a.			
Carcinogenicity:						n.d.a.			
Reproductive toxicity:						n.d.a.			
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.			
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.			
Aspiration hazard:						n.d.a.			
Respiratory tract irritation:						n.d.a.			
Repeated dose toxicity:						n.d.a.			
Symptoms:		-				n.d.a.			
Other information:						Classification according			
						to calculation procedure.			

Talc									
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes			
	t								
Skin corrosion/irritation:						Not irritant			
Serious eye damage/irritation:						Not irritant			
Respiratory or skin sensitisation:						Not sensitizising			
Germ cell mutagenicity:						Negative			
Carcinogenicity:						Negative			
Reproductive toxicity:				Rat		Negative			
Symptoms:						mucous membrane			
						irritation			

Barium sulphate										
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes				
	t									
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	IUCLID Chem. Data					
					Sheet (ESIS)					
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat						



Page 7 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g Art.: 3340

Skin corrosion/irritation:		OECD 404 (Acute	Not irritant
		Dermal	
		Irritation/Corrosion)	
Skin corrosion/irritation:		•	Not irritant
Serious eye damage/irritation:		OECD 405 (Acute Eye	Not irritant
		Irritation/Corrosion)	
Serious eye damage/irritation:			Not irritant
Respiratory or skin sensitisation:			Not sensitizising
Respiratory or skin sensitisation:			No indications of such an
			effect.
Germ cell mutagenicity:			Negative
Carcinogenicity:			Negative
Symptoms:			circulatory collapse,
			mucous membrane
			irritation

China stone									
Toxicity/effect	Endpoin	Value	Unit	Organism	Test method	Notes			
	t								
Serious eye damage/irritation:						Mechanical irritation			
						possible.			
Respiratory or skin sensitisation:						No indications of such an			
						effect.			

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Auspuff-Reparatur-Paste 200 g Art.: 3340										
Toxicity to fish:							n.d.a.			
Toxicity to daphnia:							n.d.a.			
Toxicity to algae:							n.d.a.			
Persistence and							n.d.a.			
degradability:										
Bioaccumulative							n.d.a.			
potential:										
Mobility in soil:							n.d.a.			
Results of PBT and							n.d.a.			
vPvB assessment										
Other adverse effects:							n.d.a.			
Other information:							According to the recipe,			
							contains no AOX.			

Talc							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:			< 0,1	%			

Barium sulphate							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to daphnia:	EC50	48h	32	mg/l	Daphnia magna		
Persistence and							Not relevant for inorganic
degradability:							substances.
Results of PBT and							n.a.
vPvB assessment							
Water solubility:			<0,01	mg/l			Insoluble 20°C, DIN EN
							ISO 787-8
Water solubility:			<0,01	g/l			Insoluble

China stone							
Toxicity/effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	>1000	mg/l			



Page 8 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

Toxicity to daphnia:	EC50	>1000	mg/l		
Toxicity to algae:	IC50	>1000	mg/l		
Persistence and					Not relevant for inorganic
degradability:					substances.
Water solubility:					Insoluble

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no .:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2001/118/EC, 2001/119/EC, 2001/573/EC)

08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances

Recommendation:

Pay attention to local and national official regulations

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations

15 01 04 metallic packaging

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

UN number: n.a.

Transport by road/by rail (ADR/RID)

UN proper shipping name:

Transport hazard class(es):

Packing group:

Classification code:

LQ (ADR 2013):

LQ (ADR 2009):

n.a.

n.a.

Environmental hazards:

n.a.

Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

UN proper shipping name: Transport hazard class(es): Packing group:

Marine Pollutant: n.a

Transport by air (IATA)

Environmental hazards:

UN proper shipping name:
Transport hazard class(es):
Packing group:

n.a.

Environmental hazards: Not applicable

Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

n.a.

n.a.

Not applicable



(GB)

Page 9 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

For classification and labelling see Section 2.

Observe restrictions:

Directive 2010/75/EU (VOC):

n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

These details refer to the product as it is delivered.

Revised sections:

8

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids

CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques

CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level

DOC Dissolved organic carbon
DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency



Page 10 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

European Economic Area FFA EEC **European Economic Community**

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

ΕN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

et cetera etc. ΕU European Union

EWC European Waste Catalogue

Fax. Fax number gen. general

GHS

Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association

Intermediate Bulk Container IBC

IBC (Code) International Bulk Chemical (Code)

Inhibitory concentration IC.

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration

Lethal Dose of a chemical ΙD LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

Limited Quantities IΩ

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av. not checked n.c. n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic

Chemical product category PC

PΕ Polyethylene

PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential

parts per million PROC Process category PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List REACH-IT List-No. Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature



(GB)

Page 11 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revised on / Version: 04.09.2014 / 0009

Replaces revision of / Version: 13.02.2013 / 0008

Valid from: 04.09.2014 PDF print date: 04.09.2014 Auspuff-Reparatur-Paste 200 g

Art.: 3340

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 \circledcirc by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.